



www.auraadesign.co.uk

KINGSLEY

Desk



Kingsley

Kingsley






Managerial system with a strong character and multiplicity of configurations and variants: two different structures and various types of tops to customise each project.



Kingsley SYNOPTIC GRID

h 74 cm

* w. 200 cm also with d. 100 cm



w 80÷200 cm
d 60 cm

w 160÷200 cm
d 80 cm

w 180÷200 cm
d 100 cm






w 160÷200 cm
d 80 cm

w 180÷200 cm
d 100 cm

s 1,2-1,8-3,8 cm

h 2 cm

h 74 cm



w 70 cm
d 50 cm

w 140 cm
d 80 cm






w 80÷120 cm
d 60 cm

s 1,2-1,8-3,8 cm

h 30 cm

h 40 cm

h 54 cm



w 118,5-138,5-158,5 cm
d 1,8 cm

w 98,5-118,5-138,5 cm
d 1,8 cm





w 60-120 cm
d 60 cm

w 167,8 cm
d 56,2 cm

h 54 cm

h 58,5 cm

h 54 cm




w 209,5 cm
d 56,2 cm

w 44,3 cm
d 56,2 cm


w 127,7 cm
d 56,2 cm

Kingsley SYNOPTIC GRID


h 73,7 cm




w 102,4 cm
d 46 cm



w 202,4 cm
d 46 cm




w 102,4 cm
d 46 cm



w 202,4 cm
d 46 cm


h 124,9 cm

h 74 cm




w 100 cm
d 100 cm


w 124 cm d
d 124 cm



w 164 cm
d 164 cm



w 124 cm
d 124 cm



w 240 cm
d 124 cm

s 1,2-3,8 cm




s 1,8-3,8 cm




s 1,2-1,8-3,8 cm




h 74 cm



w 248 cm
d 124 cm



w 372 cm
d 124 cm



w 372 cm
d 124 cm


s 1,2-1,8-3,8 cm




s 1,8-3,8 cm



s 1,2 cm



w 280-300-320 cm
d 124-164 cm







w 440-480 cm
d 124-164 cm


s 1,8-3,8 cm



Kingsley TECHNICAL FEATURES



Telescopic



Fixed



• Melamine top:





made of 18 - 38 mm thick chipboard covered with decorative paper impregnated with melamine resins, edged on the perimeter with 2 mm thick solid abs.
Rounded, 2 mm radius.
Density 620 Kg / m³
Formaldehyde emission class Carb phase II
Fire reaction class: 2.

• Glass top:

made from 12 mm-thick toughened glass with a shiny rounded edge; the surface below is sanded or can be lacquered in various colours. The glass tops are fixed to the structure using suction cups.

• Beams:

the legs are connected by a pair of telescopic or fixed beams made with 40 x 40 mm square section drawn tubes. At the ends of the beams are inserted the hooking elements to the portal legs in transparent abs;
the extension of the telescopic beams varies from 800 to 1000 mm. - from 1000 to 1200 mm. from 1200 to 1800 mm. - from 1800 to 2400 mm. The extension of the fixed beams is 1400 mm. - 1600 mm. - 1800 mm. - 2000 mm.





• A. Double span structure:

made from 2 mm-thick drawn steel tubes aluminium-coloured, 70 x 30 mm, to which 2 square shaped legs, 100 x 100 mm, are connected, and made from melamine wood obtained with folding technology in colours matching the tops. The intermediate support legs at the centre of the meeting tables are positioned further back to allow use of the entire top surface. All the legs have 10 mm height regulating feet.



• B. Panelled structure:

further to the square support leg version, it is also available a panel leg which is 100 mm thick. The leg is made from the same technology used for the square legs that are fixed to the steel beam to create a single, solid support element. All the legs have 10 mm height regulating feet.


Kingsley CONSTRUCTION FEATURES



• Desks abacus:




• Bench abacus



• **Desk with hanging return:**

is an add-on module 60/80 cm deep fixed to the main desk by means of molded joints in glass-filled ABS and steel plates.

N 2 clips are also supplied which, hooked to the beams, guarantee the coplanarity of the tops



• **Bridge desk on service cabinet:**



80/100 cm deep desk that lays on a service unit. They can be mounted both on the right and on the left. Containers with different dimensions with no pre-holes on the top. The user can choose position of the desk to his liking.

End leg can be:

- total bridged;
- one reduced leg.

During assembly, the legs can be placed simply or fixed after drilling the furniture on site using a metric screw.

Kingsley **ACCESSORIES**




• **Modesty panels:**

made of 18 mm thick melamine (density 620 kg / mc class and 1 with low formaldehyde emission according to CARB standards, fire reaction class 2). The modesty panels have side brackets that hook onto the beam with a clamp.

• **Leather desk pad:**

Kingsley **DESKTOP ELECTRIFICATION**




Ø 8 cm

Square grommet plug



Ø 8 cm

Round cable grommet



Ø 8 cm

Versapad
n.1 USB "A", n.1 USB
"C" n.1 electric socket




Ø 8 cm

Wireless charger




26X11,6 cm

Plastic top access



35X10 cm

Socket block for
n.1 USB "A", n.1 USB "C"
n.3 electrical sockets



26,2X12,3 cm


Double-sided top
access




Ø 3,5 cm

USB charger
01 n.2 USB


Kingsley **UNDER DESKTOP ELECTRIFICATION**




Cable tray in chrome



Vertebra cable guide with brush
strip and base



Cable tray metal sheet











Cable vertebra




Fabric cable vertebra

Pedestals and service modules • **SYNOPTIC GRID**

H: 58,5 cm		H: 54 cm	
			
w 44,3 d cm 56,2 cm	w 44,3 d cm 56,2 cm	w 127,7 cm d 56,2 cm	w 127,7 cm d 56,2 cm
			
w 167,8 cm d 56,2 cm	w 167,8 cm d 56,2 cm	w 209,5 cm d 56,2 cm	w 209,5 cm d 56,2 cm

Pedestals and service modules • **TECHNICAL FEATURES**




• Pedestals and service modules:

structure made of 18 mm thick chipboard (weight 620 Kg per m³, class E1 with low formaldehyde emission, class 2 fire reaction according to ISO standards). The fronts are 18 mm thick, the backs are structural and made of made of 12 mm thick chipboard (weight 620 Kg per m³, class E1 with low formaldehyde emission, class 2 fire reaction according to ISO standards), top and side panels are 12 mm thick. The doors are fitted with anticorrosion treated hinges with an opening of 105° and soft slow closure, the locks are a cylindrical Yale type with articulated key grip. Top, fronts, doors, backs and side panels are edged along the perimeter with 1 mm ABS and 2 mm radius. 1 pair of closing sides are always compulsory. The handles are ABS colour aluminium. The drawers are applied with guides or with simple sliding extraction on self-lubricating wheels with soft closure or telescopic extraction metal guides with integrated soft closure for filing cabinets, equipped with anticorrosion treated ball carriage, made of folded sheet metal with an 8/10 thickness and painted with epoxy powders. A stationary drawer is always supplied (apart from furniture without a lock), equipped with simple sliding extraction guides on small self-lubricating wheels. Appropriate drilling along the side edges allows the installation of optional accessories, such as horizontal separators and oblique file holder separators. 33 and 39 cm files can be hung from the file hanger frame. The drawers are equipped with 5 cm diameter swivel wheels, 2 of which with a brake; the filing cabinets have the 5th wheel with a function to prevent overturning; the service modules are equipped with Ø52 x h.18 mm feet with adjustable foot inside the furniture. The furniture can also be positioned on 5 cm diameter swivel wheels, 2 of which with a brake. The filing cabinets have the 5th wheel with a function to prevent overturning. Some compositions are equipped with a technical module with CPU port and cable passage designed to hang under the desk to make maximum use of less accessible areas.

Pedestals and service modules • CONSTRUCTION FEATURES

• Internal measurements



Pedestals and service modules • ACCESSORIES



- Stationery tray




- 5-wheel set (2 with brake)
- 5-wheel set+1 for filing cabinet (2 with brake)




- Horizontal separator for metal drawer

Credenza • SYNOPTIC GRID


H: 74 cm




w 102,4 cm
d 46 cm



w 102,4 cm
d 46 cm



w 202,4 cm
d 46 cm




w 202,4 cm
d 46 cm


H: 125 cm




w 102,4 cm
d 46 cm



w 102,4 cm
d 46 cm



w 202,4 cm
d 46 cm



w 202,4 cm
d 46 cm

Credenza • TECHNICAL FEATURES

• Credenza:

body made of 18 mm thick chipboard (weight 620 Kg per m³, class E1 with low formaldehyde emission, class 2 fire reaction according to ISO standards) edged with melamine paper on 4 sides. Top and side panels are in 12 mm thick and the edge along the perimeter sides is 1 mm thick – 2 mm radius rounded ABS. Doors made of 18 mm melamine, fitted with anticorrosion treated hinges with an opening of 105°, the locks are a cylindrical Yale type with articulated key grip. The handles are made of ABS with aluminium finish. Glass doors made of 4 mm tempered etched or coloured glass, equipped with anodized extruded aluminium perimetrical frame or painted white or black; lock and hinges at 170° cannot be mounted on these doors. The furniture is positioned on an 18 mm thick melamine base, supported by feet made of chrome-coloured 40x40xh.195mm square ABS.

Credenza • TECHNICAL FEATURES



foot



lock with removable cam




pair of foldable keys



no-bending base



structural back panel 10 mm




25 mm


shelf with support



door with duster




door with levelling hinge




110° slow-motion hinge
for wooden doors

Credenza • CONSTRUCTION FEATURES



Kingsley FINISHES


STRUCTURE



• Metal




LEVELLING FOOT



• Plastic



TOPS, LEGS, MODESTY PANEL




• Melamine



• Glass (only tops)



Service modules • FINISHES




• Melamine (only internal frame)




• Melamine (top, sides, fronts, doors)



HANDLES



• Metal (handles)



• Plastic (handles)



Credenza • CONSTRUCTION FEATURES



- 1 TOP AND
- 2 SIDES BASE
- 3 DOORS
- 4 HANDLES
- 5 FOOT
- 6 FRAME

1



melamine (Laminate)

4



handles



knob for glass door with
standard frame

1 • Melamine

NC



RN



2 • Melamine

MK




4 5 • Plastic

NE



BP



KR



6 • Melamine

MK



BP



Credenza • FINISHES




3 • Melamine




3 4 • Lacquered matt



3 • Glass



3 • Metal (frame of glass doors)



aura design



Hub Spaces, 582 Honeypot Lane, Stanmore, HA7 1JS, UK
www.auraadesign.co.uk
020 3915 8008
info@auraadesign.co.uk